

45 M3 SINGLE TIRES LPG SEMI TRAILER

LPG GROUP



TECHNICAL SPECIFICATION

45 M3 SINGLE TIRES SEMI TRAILER


45 m³ LPG TRANSPORT TANK TECHNICAL DETAILS:


BRAND	RAM
TANKTYPE	Horizontal Cylindrical
PROJECT CODE	AD-Merkblatter / EN 13445
DESIGN TEMPERATURE	Min - 20°C/ max+70°C
DESIGN PRESSURE	17,5 bar
TEST PRESSURE	26,5 bar
MATERIAL	P355 GH or P355NH
HEADTYPE	Elipsoidal
EXTERNAL TANK	45 m 3 2.400 m m
DIAMETER	
BODY TANK THICKNESS	45 m 3 10 m m
HEAD TANK THICKNESS	45 m 3 12 m m
TOTAL LENGTH OF TANK	45 m 3 11.200 m m
CORROSION	1 m m
PUMP	CORKEN PUMP
TANKVOLUME	45 m 3
EQUIPMENT TANKS OVER	Hydraulic Operator 1 unit
	2 "Bali Valves 2 units BATU
	2" Hydraulic valves 1 units ATILIM
	3" Hydraulic valves 1 unit ATILIM
	2 "Safety Vaive 2 units ATILIM
	Rotogauge (Rotary Level Indicator) 1 unit
	ATILIM Glycerine pressure gauge (0-25 bar), 11 63 1 unit PAKKENS Thermometer (-30 / 60 °C) 1163 1 unit PAKKENS
	Acme Filler Cap 2 units ATILIM
	Manhole 1 unit 16"
Blasting and Painting	Fliter 1 unit Before painting, the Tank will be sand blasted with SA 2.5 quality
Blasting and Painting	Before painting, the Tank will be sand blasted with SA 2.5 quality
Blasting and Painting	
Blasting and Painting Control (Inspection and	Before painting, the Tank will be sand blasted with SA 2.5 quality undercoat & polyurethane based white topcoat applied providing a
Control (Inspection and	Before painting, the Tank will be sand blasted with SA 2.5 quality undercoat & polyurethane based white topcoat applied providing a total thickness of min. 150 microns. COLOUR: WHITE
	Before painting, the Tank will be sand blasted with SA 2.5 quality undercoat & polyurethane based white topcoat applied providing a total thickness of min. 150 microns. COLOUR: WHITE All tests & inspections mentioned below will be carried aut
Control (Inspection and	Before painting, the Tank will be sand blasted with SA 2.5 quality undercoat & polyurethane based white topcoat applied providing a total thickness of min. 150 microns. COLOUR: WHITE All tests & inspections mentioned below will be carried aut under the control of third party & certified by the same
Control (Inspection and	Before painting, the Tank will be sand blasted with SA 2.5 quality undercoat & polyurethane based white topcoat applied providing a total thickness of min. 150 microns. COLOUR: WHITE All tests & inspections mentioned below will be carried aut under the control of third party & certified by the same authority.
Control (Inspection and	Before painting, the Tank will be sand blasted with SA 2.5 quality undercoat & polyurethane based white topcoat applied providing a total thickness of min. 150 microns. COLOUR: WHITE All tests & inspections mentioned below will be carried aut under the control of third party & certified by the same authority. Checking & approval of design & calculations, Material inspection & stamp transferring seperately, Visual & dimensional inspection plate orientation,
Control (Inspection and	Before painting, the Tank will be sand blasted with SA 2.5 quality undercoat & polyurethane based white topcoat applied providing a total thickness of min. 150 microns. COLOUR: WHITE All tests & inspections mentioned below will be carried aut under the control of third party & certified by the same authority. Checking & approval of design & calculations, Material inspection & stamp transferring seperately, Visual & dimensional inspection plate orientation, Head control,
Control (Inspection and	Before painting, the Tank will be sand blasted with SA 2.5 quality undercoat & polyurethane based white topcoat applied providing a total thickness of min. 150 microns. COLOUR: WHITE All tests & inspections mentioned below will be carried aut under the control of third party & certified by the same authority. Checking & approval of design & calculations, Material inspection & stamp transferring seperately, Visual & dimensional inspection plate orientation, Head control, Radiographic control,
Control (Inspection and	Before painting, the Tank will be sand blasted with SA 2.5 quality undercoat & polyurethane based white topcoat applied providing a total thickness of min. 150 microns. COLOUR: WHITE All tests & inspections mentioned below will be carried aut under the control of third party & certified by the same authority. Checking & approval of design & calculations, Material inspection & stamp transferring seperately, Visual & dimensional inspection plate orientation, Head control, Radiographic control, Penetrate dye test,
Control (Inspection and	Before painting, the Tank will be sand blasted with SA 2.5 quality undercoat & polyurethane based white topcoat applied providing a total thickness of min. 150 microns. COLOUR: WHITE All tests & inspections mentioned below will be carried aut under the control of third party & certified by the same authority. Checking & approval of design & calculations, Material inspection & stamp transferring seperately, Visual & dimensional inspection plate orientation, Head control, Radiographic control, Penetrate dye test, Hydrostatic test
Control (Inspection and	Before painting, the Tank will be sand blasted with SA 2.5 quality undercoat & polyurethane based white topcoat applied providing a total thickness of min. 150 microns. COLOUR: WHITE All tests & inspections mentioned below will be carried aut under the control of third party & certified by the same authority. Checking & approval of design & calculations, Material inspection & stamp transferring seperately, Visual & dimensional inspection plate orientation, Head control, Radiographic control, Penetrate dye test, Hydrostatic test The reports of the A/M tests & inspections will be presented to the
Control (Inspection and	Before painting, the Tank will be sand blasted with SA 2.5 quality undercoat & polyurethane based white topcoat applied providing a total thickness of min. 150 microns. COLOUR: WHITE All tests & inspections mentioned below will be carried aut under the control of third party & certified by the same authority. Checking & approval of design & calculations, Material inspection & stamp transferring seperately, Visual & dimensional inspection plate orientation, Head control, Radiographic control, Penetrate dye test, Hydrostatic test The reports of the A/M tests & inspections will be presented to the customer together with the inspection certificate of teh tank
Control (Inspection and	Before painting, the Tank will be sand blasted with SA 2.5 quality undercoat & polyurethane based white topcoat applied providing a total thickness of min. 150 microns. COLOUR: WHITE All tests & inspections mentioned below will be carried aut under the control of third party & certified by the same authority. Checking & approval of design & calculations, Material inspection & stamp transferring seperately, Visual & dimensional inspection plate orientation, Head control, Radiographic control, Penetrate dye test, Hydrostatic test The reports of the A/M tests & inspections will be presented to the















TUN



Tiiv'



RAM İTHALAT İHRACAT İNŞAAT NAKLİYAT SANAYİ VE TİCARET LİMİTED ŞİRKETİ Konya Organize Sanayi Bölgesi Gönülveren Sok No: 20/5 Selçuklu/ KONYA (9 info@lramtreyler.com

(ffi) www.ramtreyler.com

(f)@ ramtreyler

RAM TREYLER . reserves the right of making changes in the technica specifications and components without making any prior notice. some components seen on the photographs and specifications seen here may not be standard features of the vehicles. There may have been some changes after publication of this document. No right can be claimed on a sing or numbers used by seller or buyer to define a product on ordering. Differences in colors are due to printing techniques.



TSEK 1



Tiiv'